CLARIFUGE - FLUID CLEANING UNIT

1,000 Gs = SUPERIOR SOLID-FLUID SEPARATION



- Centrifugal particle separation without bags or filters
- · Fluid flow rate from 3 to 15 gallons per min.
- Separable solid particle to 5 microns
- Separated solids collected capacity 40 to 50 lbs.
- Removes abrasives, machining swarf and fine chips
- Clarifies wire EDM, quench, & wire drawing fluids
- · Cleans fluid from process equipment sump
- Easy bowl cleaning by Clari-Clean bowl cleaning unit
- Compact design Including a safety lid lock
- Rugged ball bearing spindle, simple reliable belt drive



PORTABLE CLARIFUGE - OPTION

This portable turnkey system includes a Clarifuge, cart, feed pump, starter switches and disconnect and is an efficient alterative to costly central filtration systems.



CLARI-CLEAN - OPTION

The Clari-Clean unit is a compact, inexpensive, and user friendly bowl cleaner with no messy hand work required. The Clari-Clean mounts to any standard 55 gallon drum.

UNSURPASSED PERFORMANCE AND RELIABILITY



ISO 9001:2015 REGISTERED

156 Goddard Memorial Drive, Worcester, MA 01603-1260 U.S.A. (508) 754-6891 kinespin@kinefac.com www.kinespin.com